


## RB441T Uses 19 ga. wire, ties up to #7 x #7

LITHIUM-ION



## RB398 Uses 21 ga. wire, #3 x #3 up to #5 x #6

LITHIUM-ION



## RB518 Uses 21 ga. wire, #5 x #5 up to #7 x #8

LITHIUM-ION



## 19 Ga. TIE WIRE 30 COILS/BOX

TW1061T  
Regular steel wire

TW1061T-EG  
Electro galv. wire

TW1061T-PC  
Polyester-coated wire



## RB218 Uses 21 ga. wire, ties up to #3 x #3

LITHIUM-ION



## 21 Ga. TIE WIRE RB398/RB518/RB218

50 COILS/BOX  
TW898  
Regular steel wire

TW898-EG  
Electro galv. wire

TW898-PC  
Polyester-coated wire




US Made Steel  
Buy America Certified

Available in  
regular steel wire

## STANDARD EQUIPMENT

- Battery pack JPL91440A
- AC Battery charger JC925
- Plastic carry case
- Reversible belt hook (Left or Right)



## SPECIFICATIONS

Tool	RB441T
Weight	5.6 lbs.
Dimensions (H)x(W)x(L)	11 1/2" x 4 3/4" x 13"
Tying Speed	Approx. 1/2 Sec.
Ties per coil	Approx. 145 to 265
Ties per charge	Approx. 4000
Battery	JPL91440A
Voltage	DC 14.4V
Recharge Time	Approx. 40 minutes



14.4 V Lithium-ion battery (JPL91440A)



Battery charger (JC925)


## SPECIFICATIONS

Tool	RB398	RB218	RB518
Weight	5.3 lbs	5.3 lbs	5.3 lbs
Dimensions (H)x(W)x(L)	12" x 4 1/8" x 11 3/8"	12" x 4 1/8" x 10 5/8"	12" x 4 1/8" x 11 3/8"
Tying Speed	Less than 1 sec. / tie	Less than 1 sec. / tie	Less than 1 sec. / tie
Wraps per tie	3 wraps	3 wraps	3 wraps or 4 wraps
Ties per coil	Approx. 120	Approx. 170 to 210	Approx. 90 (3 wraps) Approx. 75 (4 wraps)
Ties per charge	Approx. 2,600 ties	Approx. 3,000 ties	Approx. 2,400 ties (3 wraps) Approx. 2,200 ties (4 wraps)
Battery	JPL91440A (Lithium-ion Battery)		
Voltage	DC 14.4V		
Recharge Time	Approx. 40 minutes		

## STANDARD EQUIPMENT

RB398/RB518/RB218

- Battery pack JPL91440A
- AC Battery charger JC925
- Plastic carry case
- Reversible belt hook (Left or Right)



## OPTIONAL EQUIPMENT

Extension bar (JE200)

Tool cover (JT450)



14.4 V Lithium-ion battery (JPL91440A)



Battery charger (JC925)